


MEASURING DEVICE FOR FINE LEAKAGE OF VALVE

Publication number: JP59176643
Publication date: 1984-10-06
Inventor: TERADA MASABUMI; NAKAMURA TETSUO; MURAKAWA SHINICHI
Applicant: MITSUBISHI HEAVY IND LTD
Classification:
- **international:** G01M3/24; G01M3/24; (IPC1-7): F17D5/06
- **European:** G01M3/24
Application number: JP19830050265 19830325
Priority number(s): JP19830050265 19830325

Report a data error here

Abstract of JP59176643

PURPOSE:To measure fine leakage easily and quantitatively by allowing an acoustic sensor to detect an acoustic signal generated when fine liquid or gas leaks from a valve in a closed state, and converting its detection signal into a leak flow rate and outputting it. **CONSTITUTION:**When a leak occurs to the valve 1, an acoustic signal corresponding to the leak is generated at the leak part. This is detected by the acoustic sensor 2 and amplified by a signal amplifier 3, and an incorporated filter removes frequency components except in the frequency band of the acoustic signal generated by the leak. Further, a background noise in the signal from the acoustic sensor 2 is removed to improve the S/N ratio. The signal after the noise removal is inputted to an RM meter 4 and converted into an RMS value. The output of the RMS meter 4 is inputted to an RMS value/leak flow rate converter 5 and converted into leakage. A signal indicating the leakage is sent to an output part 6 to perform display and recording and generate an alarm when the leakage exceeds a set value. Consequently, fine leakage is measured easily, quantitatively, and automatically.



Data supplied from the esp@cenet database - Worldwide